

**Technical Specifications**

- Capacity: From 500 kg to 3000 kg
- Travel: 500 to 1500 mm
- Closed Height: 85 - 120 mm
- Length: 1200 - 1800 mm
- Width: 800 - 1350 mm
- CE-Marked and comply with European Norms and Standards
- 2 Safety lock for maintenance
- Safety trip bar in aluminum
- Available in Ral Colors
- Large in-house lift table stock for immediate delivery



**NOTE: ALL DETAILS CAN BE CUSTOMIZED FOR YOUR NEEDS**

OndLift is biggest manufacturer company in Lifting Tables sector in Turkey and exporting 32 countries.

OndLift' s low profile lift tables is a very low closed height, which eliminates the need for a pit installation.

OndLift' s Lift Tables series can be the manufacturing with different kind of options, such as mobile base, loading flaps, guard rails, rollers. (for detailed information, please check Lift Table Accessories Datasheet ).

OndLift' s Lift Table series, have a vital role to create ergonomic and safe working conditions. Can be the best selection of challenging situations, high lifting capacities, intense pace of work.

For more information [www.ondlift.com](http://www.ondlift.com)

**TUB.1****TUB.2**

Art No	Model	Capacity kg	Platform Dimension LxW mm x mm	Lift Stroke H mm	Closed Height C mm	Lift Time sec	Motor kW	Weight kg
70.06.001	TUB.1/06-08*	600	1450 x 1140	760	85	21	0,75	210
70.06.002	TUB.1/06-10*	600	1610 x 1140	970	85	25	0,75	230
70.10.003	TUB.1/10-08*	1000	1450 x 1140	760	85	21	0,75	280
70.10.004	TUB.1/10-10*	1000	1610 x 1140	970	85	25	0,75	300
70.15.005	TUB.1/15-08*	1500	1450 x 1140	760	85	25	1,1	310
70.15.006	TUB.1/15-10*	1500	1610 x 1140	970	85	30	1,1	330
70.20.007	TUB.1/20-08*	2000	1450 x 1140	760	100	28	1,5	330
70.20.008	TUB.1/20-10*	2000	1610 x 1140	970	100	32	1,5	350
75.06.001	TUB.2/06-08*	600	1450 x 1140	760	85	21	0,75	230
75.06.002	TUB.2/06-10*	600	1610 x 1140	970	85	25	0,75	250
75.10.003	TUB.2/10-08*	1000	1450 x 1140	760	85	21	0,75	350
75.10.004	TUB.2/10-10*	1000	1610 x 1140	970	85	25	0,75	380
75.15.005	TUB.2/15-08*	1500	1450 x 1140	760	85	25	1,1	350
75.15.006	TUB.2/15-10*	1500	1610 x 1140	970	85	30	1,1	380
75.20.007	TUB.2/20-08*	2000	1450 x 1140	760	100	28	1,5	400
75.20.008	TUB.2/20-10*	2000	1610 x 1140	970	100	32	1,5	420


\* External power pack

## Load Factors Accordance with EN1570-1

Maximum load refers to the load being uniformly distributed over the entire platform area in accordance with EN 1570 the basic requirements are;



100 % of maximum load uniformly distributed over the entire platform.



50 % of load weight uniformly distributed over half of the platform area lengthwise.



33 % of load weight uniformly distributed over half of the platform area sideways.

## Technical Drawing

- L:** Platform Length
- W:** Platform Width
- C:** Closed Height
- H:** Stroke
- C + H:** Maximum Height

## Technical Drawing

- L:** Platform Length
- W:** Platform Width
- C:** Closed Height
- H:** Stroke
- C + H:** Maximum Height

### ONDLIFT Mak. San. Tic. Ltd. Şti

**Factory:** Organize Sanayi Bolgesi 2004 Cad. No: 4  
Turgutlu/Manisa/TURKEY

**Showroom:** İmes San. Sit. C.302 Sk. No:13  
Y.Dudullu/Umraniye/Istanbul/TURKEY

Tel: 0090 236 332 5050

ondlift@ondlift.com

Product specifications are subject to change without any notice or obligation. The photographs and/or drawing in this documents are for illustrative purpose only. All productions of OndLift, manufacturing for CE standards.

**Turkey**  
Discover  
the potential

Onder Lift Celik



**43rd Years Anniversary**

Your warehouse partner

Onder Group Companies